

### **Basic Data**

Vessel's type AHTS Built 2011

Classification society IACS member

**DP class** DP1



### **General Characteristics**

| LOA                      | 71.50 m                       |
|--------------------------|-------------------------------|
| Beam                     | 16.60 m                       |
| Depth                    | 7.20 m                        |
| Draft (design)           | 4.50 m                        |
| Draft (max)              | 5.90 m                        |
| Tonnage (GT / NT)        | 2,588 / 776                   |
| Deadweight (4.5 m draft) | 875 t                         |
| Deadweight (5.9 m draft) | 2,278 t                       |
| Speed (max)              | 14 kn                         |
| Fuel type                | MDO                           |
| Accommodation            | 40 pax (20 cabins) + hospital |

### **Engine Room**

| ME                         | 2 x 2,920 kW @ 800 rpm / MAN B&W 8L27/38                       |
|----------------------------|--|
| Generator                  | 2 x 425 kW / C 18 @ 440 V / Ph 60 Hz                           |
| Shaft generator            | 2 x 1,200 kW @ 440 V / 3Ph 60 Hz / Leroy Somer                 |
| <b>Emergency generator</b> | 1 x 122 kW @ 440 V / 3Ph 60 Hz / Volvo Penta                   |
| Propeller                  | 2 x CPP / 3.4 m / in nozzles / 2 independent high-lift rudders |
| Bow thruster               | 2 x 515 kW / CP / 78 kN  |
| Stern thruster             | 1 x 515 kW / CP / 78 kN  |

## **Deck Equipment**

| Tow winch      | 2 double drum (waterfall) / 200 t stall pull / 300 t brake hold |
|----------------|---|
| - wire drum    | 2 x 1,500 m / 56 mm diam wire                                   |
| - storage drum | 1 x 1,500 m / 56 mm diam wire / 5.5 t @ 0-30 m/min              |
| Tugger winch   | 2 x 10 t / up to 16 m/min                                       |
| Shark jaws     | 1 x Triplex H200 / SWL 200 t                                    |
| Tow pin        | 1 x Triplex S115 / SWL 115 t                                    |
| Stern roller   | 1 x SWL 300 t / 6 m x 2 m diam                                  |
| Grapnel hook   | 1 x 110 t   |
| J hook         | 1 x 110 t   |
| Windlass       | 1 x 10 t / 9 m/min / 2 x 2,140 kg anchor                        |
| Capstan        | 2 x 5 t / 0-15 m/min  |
| Deck crane     | 1 x knuckle boom / 5 t @ 18 m                                   |



# Cargo Deck

Clear deck space 450 sqm

**Deck strength** 10 t/sqm (for area abt 160 sqm)

Deck cargo (max) 900 t

**Reefer plugs** 2 x 440 V and 2 x 220 V

## Tanks (Capacities)

| Fuel        | 763 cbm / pump: 1 x 150 cbm/hr   |
|-------------|----------------------------------|
| FW          | 541 cbm / pump: 1 x 150 cbm/hr   |
| Drill water | 1,524 cbm / pump: 1 x 150 cbm/hr |
| Mud         | 448 cbm / pump: 1 x 100 cbm/hr   |
| Brine       | 312 cbm / pump: 1 x 100 cbm/hr   |
| Dry bulk    | 250 cbm (4 tanks) / 6 bar        |
| Foam        | 10 cbm / FiFi 1                  |
| Dispersant  | 13 cbm / oil recovery            |

### **Electronics**

all modern